

Type - AF962

10 Bar Oil Suction and Delivery Hose



Part No	Internal Dia (inch)	Internal Dia (mm)	Outside Dia (mm)	W/P psi	Weight kg/mtr
AF962-12	3/4	19	29	150	0.50
AF962-16	1	25	35	150	0.63
AF962-18	1.1/8	28	38	150	0.64
AF962-20	1.1/4	32	43	150	0.86
AF962-24	1.1/2	38	50	150	1.10
AF962-28	1.3/4	45	57	150	1.28
AF962-32	2	51	63	150	1.43
AF962-36	2.1/4	60	72	150	1.65
AF962-40	2.1/2	63	77	150	1.98
AF962-48	3	76	90	150	2.43
AF962-56	3.1/2	90	106	150	3.28
AF912-64	4	102	119	150	3.92
AF962-80	5	127	145	150	5.11
AF912-96	6	152	172	150	6.77

Structure :

Rubber hose with smooth black inner tube, textile yarn and embedded metal spiral reinforcement, copper wire to ensure the electric conductivity, antistatic smooth, cloth impression, black, oil, abrasion and weathering resistant cover.

Application :

Fuels having an aromatic content up to 40% and mineral oils suction and delivery hose. Suitable for loading and unloading of tank trucks, refineries and maintenance shops.

Specification :

According to ISO1307

Working Temperature :

-30°C+100°C(-22°F+210°F)

Standard Lengths :

Maximum lengths up to 61mtr(200 ft)

Branding :

AN-FLEX Type 962 10 BAR PETROLEUM S & D HOSE
Tube - Black, Cover - Black with Red stripe

Type - AF963

16 Bar Oil Suction and Delivery Hose



Part No	Internal Dia (inch)	Internal Dia (mm)	Outside Dia (mm)	W/P psi	Weight kg/mtr
AF963-12	3/4	19	32	235	0.68
AF963-16	1	25	38	235	0.84
AF963-20	1.1/4	32	44	235	0.93
AF963-24	1.1/2	38	51	235	1.18
AF963-32	2	51	63	235	1.79
AF963-40	2.1/2	63	79	235	2.26
AF963-48	3	76	91	235	2.56
AF963-64	4	102	121	235	4.33

Structure :

Rubber hose with smooth, black inner tube with normal high tenacity textile yarn and embedded metal spiral reinforcement, electrically conductive with copper wire, smooth, cloth impression, black, oil, abrasion, weathering and flame resistant cover.

Application :

Fuels having high content of aeromatic up to 50% suction and delivery hose. Suitable for aeroplane service tank-trucks and for marine refilling operation.

Specification :

According to ISO1307

Working Temperature :

-30°C+100°C(-22°F+212°F)

Standard Lengths :

Maximum lengths up to 61 mtr(200 ft)

Branding :

AN-FLEX Type 963 16 BAR PETROLEUM S & D HOSE
Tube - Black, Cover - Black with Brown stripe