

## Type - AF922

### 10 Bar Water Discharge Hose - LF -



**Structure :**

Rubber light collapsible hose with smooth black inner tube, textile yarn reinforcement, cloth impression, black, abrasion and weathering resistant rubber cover.

**Application :**

Water and inert fluid delivery hose for submerged pump irrigation system, as well as for waste water and natural liquid fertilizer systems.

**Specification :**

According to ISO 1307

**Working Temperature :**

-40°C+90°C (-40°F+194°F)

**Standard Lengths :**

Maximum lengths up to 61mtr(200 ft)

**Branding :**

AN-FLEX Type 922 10 BAR WATER DISCHARGE - LF -  
Tube - Black, Cover - Black

Part No	Internal Dia (inch)	Internal Dia (mm)	Outside Dia (mm)	W/P psi	Weight kg/mtr
AF922-20	1.1/4	32	38	150	0.54
AF922-24	1.1/2	38	44	150	0.63
AF922-32	2	51	58	150	0.74
AF922-40	2.1/2	63	70	150	0.85
AF922-48	3	76	83	150	1.08
AF922-64	4	102	110	150	1.65
AF922-80	5	127	135	150	2.04
AF922-96	6	152	162	150	3.06
AF922-128	8	203	216	150	5.30

## Type - AF931

### 10 Bar 2 Ply Sandblasting



**Structure :**

Conductive rubber hose, smooth, black inner tube, textile yarn reinforcement, cloth impression, black, abrasion and weathering resistant rubber cover.

**Application :**

Sand, powders and grit mixed with air delivery hose, suitable for sandblasting equipments as well as for the delivery of metal grit and foundry waste. Made of conductive rubber to ensure static electricity dissipation.

**Specification :**

Abrasion loss value according to DIN53516

**Working Temperature :**

-40°C+90°C(-40°F+194°F)

**Standard Length :**

Maximum length of 61 mtr(200 ft)

**Branding :**

AN-FLEX Type 931 10 BAR SANDBLAST HOSE  
Tube - Black, Cover - Black

Part No	Internal Dia (inch)	Internal Dia (mm)	Outside Dia (mm)	W/P psi	Weight kg/mtr
AF931-08	1/2	13	27	150	0.51
AF931-12	3/4	19	33	150	0.66
AF931-16	1	25	40	150	0.88
AF931-20	1.1/4	32	48	150	1.16 y
AF931-24	1.1/2	38	54	150	1.33
AF931-32	2	51	73	150	2.20